

# Technical Data Sheet

## NEW & IMPROVED TWIN SOAK

### Alkaline Presoak

#### Description

A cost effective alkaline presoak. It can be used in other applications such as tire and wheel cleaners and degreasers. Available in liquid concentrate or Twin Packs.

#### Features

Low cost  
Great Show  
Available in Twin Packs for economical storage and transport  
Tough on window masks  
Great on tires and white walls  
Versatile crossover application  
Freeze/thaw stable

#### Applications

In touchless applications use at dilutions of 36-50:1 (2.50-3.50oz/gal). Start with tan tip. Titrate 10 drops. For tire and wheel applications use between 5-17:1. Start with a Beige tip.

#### Specifications

Color: RED

Fragrance: NONE

Foam: WHITE

pH: 13.5

Proper Shipping Name:

UN3266, CORROSIVE LIQUID, BASIC,  
INORGANIC, N.O.S.(SODIUM HYDROXIDE) 8,  
II

Titration Information:

Sample Size: 8 ml.

Indicator: Phenolphthalein 0.1% solution.

Reagent: 0.5 N Hydrochloric Acid.

Directions

1. Add in 3 drops of indicator in test sample. It will turn pink.
2. Add drops of reagent until sample turns water white.

Drop Count (Titration)	Oz/Gal of water	Ratio to 1
5	1.67	76
6	2.00	63
7	2.33	54
8	2.67	47
9	3.00	42
10	3.33	37
11	3.67	34
12	4.00	31
13	4.33	29
14	4.67	26
15	5.00	25
16	5.33	23

**CAR WASH SERVICES, INC.**

**P.O. BOX 595**

**CORDOVA, TN 38088-0595**

**(901) 744-3934**

The information herein is considered accurate. Since conditions of product use are beyond our control, no warranties are expressed or implied. The suitability of the product for an intended use shall be solely up to the user.